

Pro-Rod 880H

Have you tried our new 880H Coiled Rod in your problem well?

Pro-Rod® 880H is the latest addition to the Pro-Rod® coiled rod product line that combines a high-strength material with corrosion resistant technology. This provides an economical option for thermal and conventional production in both reciprocating and PCP applications. The 880H Product provides equivalent torque values to 1 3/16" Coiled Rod without the typical problem of yielding the product in conventional transport reels. This proprietary alloy rod has proven to be effective in a client's thermal rod pumped application. With base grades like no other, 880H significantly increased the "Mean Time Between Failures" resulting in longer problem-free production cycles and increased profits for the client. See graph.

Product Specifications

- Available in 1" (25.4 mm) & 1 1/8" (28.6 mm) sizes
- Tensile Strength 155 ksi (1069 MPa) min
- Yield Strength 145 ksi (1000 MPa) min
- Torque Values
 - ▶ 1 1/8" – 2,230 ft-lbs (3,023 N-m)
 - ▶ 1" – 1,565 ft-lbs (2,122 N-m)



Coiled Rod Solutions



To learn more, please contact us at 1-780-449-7101 or email Prorodinfo@apergy.com

880H Performance in Steam Flood Field Mean Time to Failure (MTF in Days)

